



Physical-Technical Testing Institute
Ostrava - Radvanice



(1) **Supplementary EU - Type Examination Certificate No.4**

(2) **Equipment or Protective Systems Intended for Use
in Potentially Explosive Atmospheres
(Directive 2014/34/EU)**

(3) EU - Type Examination Certificate number:

FTZÚ 07 ATEX 0002U

(4) Product: **Universal instrument housing type XD-SI, XD-SIwin, XD-SILwin**

(5) Manufacturer: **Limatherm, S.A.**

(6) Address: **ul. Tarnowska 1, 34-600 Limanowa, Poland**

(7) This supplementary certificate extends EC - Type Examination Certificate No. FTZÚ 07 ATEX 0002U to apply to products designed and constructed in accordance with the specification set out in the Schedule of the said certificate but having any variations specified in the Schedule attached to this certificate and the documents therein referred to.

(8) The Physical-Technical Testing Institute, Notified Body number 1026, in accordance with Articles 17 of Directive 2014/34/EU of the European Parliament and of the Council, dated 26.02.2014, certifies that this product, as modified by this supplementary certificate, has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of products intended for use in potentially explosive atmospheres given in Annex II to the Directive.

(9) In accordance with Article 41 of Directive 2014/34/EU, EC-Type Examination Certificates referring to 94/9/EC that were in existence prior to the date of application of 2014/34/EU (20.04.2016) may be referenced as if they were issued in accordance with Directive 2014/34/EU. Supplementary Certificates to such EC-Type Examination Certificates, and new issues of such certificates, may continue to bear the original certificate number issued prior to 20.04.2016.

(10) Compliance with the Essential Health and Safety Requirements has been assured by compliance with:


EN IEC 60079-0:2018, EN 60079-1:2014, EN 60079-31:2014

(11) The marking of the product shall include the following:

 **I M2 Ex db I Mb
II 2G Ex db IIC Gb
II 2D Ex tb IIC Db**

(12) This certificate is valid till: **30.09.2024**

Responsible person:


Dipl. Ing. Lukáš Martinák
Head of Certification Body



Date of issue: 13.09.2019

Page: 1/3

This certificate is granted subject to the general conditions of the FTZÚ, s.p.

This certificate may only be reproduced in its entirety and without any change, schedule included.

Physical-Technical Testing Institute, s.p., Pikartská 1337/7, 716 07 Ostrava - Radvanice, Czech Republic
tel +420 595 223 111, fax +420 596 232 672, ftzu@ftzu.cz, www.ftzu.cz



**Physical-Technical Testing Institute
Ostrava - Radvanice**

(13)

Schedule

(14)

**Supplementary EU - Type Examination Certificate No. 4
to FTZÚ 07 ATEX 0002U**

(15) Description of the variation to the Product:

The subject of this supplementary certificate is:

- Evaluation according to the newest standards;
- Prolongation of certificate validity.

The design of empty enclosure with type of Ex-protection Ex db and Ex tb was unchanged.

The enclosure is recertified according to the standards EN IEC 60079-0:2018, EN 60079-1:2014 and EN 60079-31:2014.

(16) Report Number.: 07/0002/4

(17) Specific Conditions of Use:

1. The maximum number, size and position of threaded entries - see the application manual - document N-L3625 dated 15.07.2019.
2. A service temperature range according to model:

Housing type	Tserv.	
	VQM rubber	FKM rubber
XD- SI	-50°C to +150°C	-20°C to +200°C
XD- SIwin, XD-SILwin	-50°C to +85°C	-20°C to +85°C

3. The empty enclosure can be used for electrical equipment designed for ambient temperatures not exceed range -50°C to +85°C.
4. An apparatus installed inside of the empty enclosure can has any lay-out, which ensures, that in any cross-section area will be at least 40% of area free for group IIC and 20% for group I Mb.
5. A circuit breakers or contactors containing oil filling are not allowed to be installed inside of the empty enclosure.
6. The enclosure was verified by over pressure static test 41 bars / 10 s for XD-SI; XD-SIwin (reference pressure: 10,07 bars) and 34 bars for XD-SILwin (reference pressure: 8,32 bars).

Responsible person:


Dipl. Ing. Lukáš Martinák
Head of Certification Body



Date of issue: 13.09.2019

Page: 2/3



Physical-Technical Testing Institute
Ostrava - Radvanice

(13)

Schedule

(14) **Supplementary EU - Type Examination Certificate No. 4
to FTZÚ 07 ATEX 0002U**

(18) Essential Health and Safety Requirements:


Compliance with the Essential Health and Safety Requirements is covered by standards mentioned in clause (10) of this supplementary certificate.

(19) Drawings and Documents:

Number	Sheets	Issue	Date	Description
N-L3625	6	--	15.07.2019	Application manual
--	2	--	16.07.2019	Datasheet XD-SI
2-Z-L3586	1	d	15.07.2019	Drawing XD-SI
2-Z-L4029	1	c	15.07.2019	Drawing XD-SIwin
2-Z-L4266	1	a	15.07.2019	Drawing XD-SILwin

Responsible person:


Dipl. Ing. Lukáš Martinák
Head of Certification Body



Date of issue: 13.09.2019

Page: 3/3



(1) **Supplement No. 3 to
EC-Type Examination Certificate**

(2) **Equipment or Protective Systems Intended for Use
in Potentially Explosive Atmospheres
(Directive 94/9/EC)**

(3) EC-Type Examination Certificate Number:

FTZÚ 07 ATEX 0002U

(4) Component: **Universal instrument housing type XD-SI, XD-SIwin and XD-SILwin**

(5) Manufacturer: **Limatherm, S.A.**

(6) Address: **ul. Tarnowska 1, 34-600 Limanowa, Poland**

(7) This supplement of certificate is valid for:

- modification of certified component
- verification according to new standards
- prolongation of certificate validity


(8) Modification of certified component and any of its approved variants are specified in documentation, a list of which is mentioned in schedule of this certificate.

(9) This supplement to type examination relates only to design, examination and testing of the specified component in accordance to the directive 94/9/EC. If applicable, further requirements of the Directive apply to the manufacture and supply of this component.

(10) Safety requirements of modified parts were fulfilled by satisfying of the following standards:


EN 60079-0:2012; EN 60079-1:2007; EN 60079-31:2009

(11) Marking of component shall contain symbols:

I M2 Ex d I Mb
 **II 2G Ex d IIC Gb**
II 2D Ex tb IIIC Db

(12) This type examination certificate is valid till: **30.09. 2019**

Responsible person:


Dipl. Ing. Lukáš Martinák
Head of Certification Body



Date of issue: 05.09.2014

Page: 1/3

This supplement to certificate is granted subject to the general conditions of the FTZÚ, s.p.
This supplement to certificate may only be reproduced in its entirety and without any change, schedule included.



Physical Technical Testing Institute
Ostrava – Radvanice

(13)

Schedule

(14)

Supplement No. 3 to
EC-Type Examination Certificate N° FTZÚ 07 ATEX 0002U

(15) Description of Component:

Modification of the Universal instrument housing consists of:

- 1) Change the thickness of circlip from 2 mm to 3 mm in types of housing with window;
- 2) Using only M and NPT threads for thread holes D₁; D₂; D₃ and the length of NPT threads was changed from 13mm to 16,2mm;
- 3) Introducing new type of housing XD-SILwin.

The types of the Universal instrument housing are recertified according to standards EN 60079-0:2012; EN 60079-1:2007 and EN 60079-31:2009.

(16) Report No.: 07/0002-3

(17) Schedule of Limitations:

17.1 Service temperature according to housing type and used sealing ring:

Housing type	Tserv.	
	VQM rubber	FKM rubber
XD- SI	-50°C to +150°C	-20°C to +200°C
XD- SIwin, XD-SILwin	-50°C to +85°C	-20°C to +85°C

17.2 IP protection 66 – 68 is depend on applied cable gland (max. IP 68 / deep = 1 m);

17.3 Max. number, size and position of apertures – see (19) of this supplement;

17.4 The enclosure with Ex component certificate shall be applicated only by assumption of filling requests of the standard EN 60079-1:2009 cl.D.3.10;

17.5 The type static pressure test (four times the reference pressure):

- type XD- SI; XD-SIwin – 41 bar;
- type XD-SILwin – 34 bar.

Responsible person:


Dipl. Ing. Lukáš Martinák
Head of Certification Body



Date of issue: 05.09.2014

Page: 2/3

This supplement to certificate is granted subject to the general conditions of the FTZÚ, s.p.
This supplement to certificate may only be reproduced in its entirety and without any change, schedule included.

FTZÚ, s.p., Pikartská 1337/7, 716 07 Ostrava-Radvanice, Czech Republic,
tel +420 595 223 111, fax +420 596 232 672, ftzu@ftzu.cz, www.ftzu.cz



Physical Technical Testing Institute
Ostrava – Radvanice

(13)

Schedule

(14)

Supplement No. 3 to
EC-Type Examination Certificate N° FTZÚ 07 ATEX 0002U

17.6 Max. dissipation power for temperature class are as follow:

Max. power dissipation (W)				
T _{amb}	Temperature class T6 85°C	Pztr (W)	Temperature class T5 100°C	Pztr (W)
		For all variety of enclosures position horizontally/vertically		For all variety of enclosures position horizontally/vertically
40°C	$\Delta 0 \leq 40$ K	20,0 / 15,0	$\Delta 0 \leq 55$ K	29,0 / 24,0
55°C	$\Delta 0 \leq 25$ K	11,0 / 8,5	$\Delta 0 \leq 40$ K	20,0 / 15,0
70°C	$\Delta 0 \leq 10$ K	3,6 / 3,1	$\Delta 0 \leq 25$ K	11,0 / 8,5
85°C	N.A.	--	$\Delta 0 \leq 10$ K	3,6 / 3,1


(18) Essential Health and Safety Requirements:

Covered by standards mentioned in (10) of this supplement of certificate.

(19) List of Documentation:

Title	Drawing No.	Date	Revision
Application manual	N-L3625	11.09.2012	
Datasheet	XD-SI	11.09.2012	
Drawing No.: XD-SI	2-Z-L3586	09.02.2012	rev.c
Drawing No.: XD-SIwin	2-Z-L4029	09.02.2012	rev.b
Drawing No.: XD-SILwin	2-Z-L4266	08.11.2012	

Responsible person:



Dipl. Ing. Lukáš Martinák
Head of Certification Body



Date of issue: 05.09.2014

Page: 3/3

This supplement to certificate is granted subject to the general conditions of the FTZÚ, s.p.
This supplement to certificate may only be reproduced in its entirety and without any change, schedule included.

FTZÚ, s.p., Pikartská 1337/7, 716 07 Ostrava-Radvanice, Czech Republic,
tel +420 595 223 111, fax +420 596 232 672, ftzu@ftzu.cz, www.ftzu.cz



Supplement No. 2 to EC-Type Examination Certificate

(1)

(2)

Equipment or Protective Systems Intended for use
in Potentially Explosive Atmospheres
Directive 94/9/EC

(3) EC-Type Examination Certificate Number:

FTZÚ 07 ATEX 0002U

(4) Component: **Model XD-SI, XD-SIwin Instrument Housing**

(5) Manufacturer: **Limatherm, S.A.**

(6) Address: **ul.Tarnowska 1, 34-600 Limanowa, Poland**

(7) This supplement of certificate is valid for: - prolongation of certificate validity

(8) Modification of certified component and any of its approved variants are specified in documentation, a list of which is mentioned in the schedule of this certificate.

(9) This supplement to type examination relates only to design, examination and testing of the specified component in accordance to the directive 94/9/EC. If applicable, further requirements of the Directive apply to the manufacture and supply of this component.

(10) Safety requirements of modified parts were fulfilled by satisfying of following standards:

EN 60079-0:2009 EN 60079-1:2007 EN 60079-31:2009

(11) Marking of component shall contain symbols:

 **I M2 Ex d I Mb**

 **II 2G Ex d IIC Gb**

 **II 2D Ex t IIIC Db**

(12) This type examination certificate is valid till: **05.09.2017**

Responsible person:

Dipl. Ing. Lukáš Martinák
Head of certification body



Date of issue: 05.09.2012

Number of pages: 2
Page: 1/2

This supplement to certificate is granted subject to the general conditions of the Physical Technical Testing Institute.
This supplement to certificate may only be reproduced in its entirety and without any change, schedule included.



**Physical Technical Testing Institute
Ostrava-Radvanice**

(13)

Schedule

(14)

**Supplement No. 2 to
EC-Type Examination Certificate N° FTZÚ 07 ATEX 0002U**

(15) Description of Component:

Subject of this supplement is prolongation of certificate validity of newest standards.

Flameproof housing without changes.

(16) Report No. : 07/0002-D2 (2 pages)

(17) Schedule of limitations:

17.1 The special conditions described in main document and the supplement No.1 are valid in all whole range.

17.2 Equipment tested for lower mechanical strength for mines area (I M2 Ex d I Mb) 4J.

17.3 Maximum design gaps of flameproof joints are smaller than maximum permitted gaps according to standard. Verified values of design gaps are mentioned in documentation.

(18) Essential Health and Safety Requirements:

18.1 Covered by standards mentioned in (10) of this supplement

18.2 The additional test with sealing material were made according to the standard EN 60079-0 and related.

(19) LIST OF DOCUMENTATION

Title:	Drawing No.:	Date:
Application Manual	N-L3625	15.11.2011
XD-SI Data sheet	--	15.11.2011
XD-SI	2-Z-L3586	09.02.2012 - rev. c
XD-SIwin	2-Z-L4029	09.02.2012 - rev. b

Responsible person:

Dipl. Ing. Martinák Lukáš
Head of certification body



Date of issue: 05.09.2012

Page: 2/2

This supplement to certificate is granted subject to the general conditions of the Physical Technical Testing Institute.
This supplement to certificate may only be reproduced in its entirety and without any change, schedule included.



**Supplement No. 1 to
EC-Type Examination Certificate**

**Equipment or Protective Systems Intended for use
in Potentially Explosive Atmospheres
Directive 94/9/EC**

(3) EC-Type Examination Certificate Number:

FTZÚ 07 ATEX 0002U

(4) Component: **Model XD-SI, universal instrument housing**

(5) Manufacturer: **Limatherm, S.A.**

(6) Address: **ul. Tarnowska 1, 34-600 Limanowa, Poland**

(7) This supplement of certificate is valid for: - new model **XD-SIwin** (variant) – extension of series
- extension of Tserv for XD-SI series

(8) Modification of certified component and any of its approved variants are specified in documentation, a list of which is mentioned in the schedule of this certificate.

(9) This supplement to type examination relates only to design, examination and testing of the specified component in accordance to the directive 94/9/EC. If applicable, further requirements of the Directive apply to the manufacture and supply of this component.

(10) Safety requirements of modified parts were fulfilled by satisfying of following standards:

EN 60079-0:2006; EN 60079-1:2007; EN 61241-0:2006; EN 61241-1:2004

(11) Marking of component shall contain symbols:

 **I M 2 Ex d I
II 2G Ex d IIC
II 2D Ex tD A21**

(12) This type examination certificate is valid till: **31.03.2012**

Responsible person:


Dipl. Ing. Šindler Jaroslav
Head of certification body



Date of issue: 14.01.2009

Number of pages: 3
Page: 1/3



**Physical Technical Testing Institute
Ostrava-Radvanice**

(13)

Schedule

(14)

**Supplement No. 1 to
EC-Type Examination Certificate N° FTZÚ 07 ATEX 0002U**

(15) Description of Component:

- XD-SI win enclosure is alternatively designed with the cover with a window.
- Further is changed a lock screw from M3x6 to M4x8 on the housing XD-SI and XD-SI win.
- It is introduced additional "O" ring made from fluoroelastomer FKM, for temperature range of XD-SI housing from -20°C to +200°C.

(16) Report No. : 07/0002-D1

(17) Schedule of limitations:

17.1 T_{serv} : -20°C to +200°C for XD-SI enclosure (fluoroelastomer rubber FKM)

T_{serv} : -20°C to +85°C for XD-SIwin (fluoroelastomer rubber FKM)

T_{serv} : -50°C to +85°C for XD-SIwin (silicone rubber VQM)

17.2 The conditions, mentioned in the main document are valid in whole range.

17. Max power dissipation (W):

Max. power dissipation (W)				
T_{amb}	Temperature class T6 85°C	Pztr (W)	Temperature class T5 100°C	Pztr (W)
		Cover with window Horizontally / Vertically		Cover with window Horizontally / Vertically
40°C	$\Delta \theta \leq 40$ K	20,0 / 15,0	$\Delta \theta \leq 55$ K	29,0 / 24,0
55°C	$\Delta \theta \leq 25$ K	11,0 / 8,5	$\Delta \theta \leq 40$ K	20,0 / 15,0
70°C	$\Delta \theta \leq 10$ K	3,6 / 3,1	$\Delta \theta \leq 25$ K	11,0 / 8,5
85°C	N.A.	- / -	$\Delta \theta \leq 10$ K	3,6 / 3,1

(18) Essential Health and Safety Requirements:

Covered by standards mentioned in (10) of this supplement.

Responsible person:

Dipl. Ing. Šindler Jaroslav
Head of certification body



Date of issue: 14.01.2009

Number of pages: 3
Page: 2/3

This supplement to certificate is granted subject to the general conditions of the Physical Technical Testing Institute.
This supplement to certificate may only be reproduced in its entirety and without any change, schedule included.



**Physical Technical Testing Institute
Ostrava-Radvanice**

(13) **Schedule**

(14) **Supplement No. 1 to
EC-Type Examination Certificate N° FTZÚ 07 ATEX 0002U**

(19) **LIST OF DOCUMENTATION**

- Application manual No. N-L3625 dated 28.11.2008
- Data sheet-type XD-SI dated 09.09.2008
- Data sheet-type XD-SI win dated 09.09.2008
- Drawings No.: 2-Z-L3586 dated 27.08.2008
- Drawings No.: 2-Z-L4029 dated 09.09.2008
- Compound data sheet VR1-fluoroelastomer FKM
- Composition and technical information about Soda lime glass

Responsible person:


Dipl. Ing. Šindler Jaroslav
Head of certification body



Date of issue: 14.01.2009

Number of pages: 3

Page: 3/3

This supplement to certificate is granted subject to the general conditions of the Physical Technical Testing Institute.
This supplement to certificate may only be reproduced in its entirety and without any change, schedule included.



EC-Type Examination Certificate

(1)

(2)

Equipment or Protective Systems Intended for use
in Potentially Explosive Atmospheres
Directive 94/9/EC

(3) EC-Type Examination Certificate Number:

FTZÚ 07 ATEX 0002U

(4) Component: **Model XD-SI, universal instrument housing**

(5) Manufacturer: **Limatherm, S.A.**

(6) Address: **ul. Tarnowska 1, 34-600 Limanowa, Poland**

(7) This Component and any of acceptable variation thereto is specified in the schedule to this certificate and the documents therein referred to.

(8) The Physical Technical Testing Institute, notified body number 1026 in accordance with Article 9 of the Council Directive 94/9/EC of 23 March 1994, certifies that this equipment or protective system has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of equipment and protective systems intended for use in potentially explosive atmospheres given in Annex II to the Directive.

The examination and test results are recorded in confidential Report N°

07/0002 dated January 2007

(9) Compliance with Essential Health and Safety Requirements has been assured by compliance with:

EN 60079-0:2006; EN 60079-1:2004; EN 61241-0:2006; EN 61241-1:2004

(10) The sign „U” placed after the certificate number indicates that this certificate must not be mistaken for a certificate intended for an equipment or protective system. This partial certification may be used as a basis for certification of an equipment or protective system.

(11) This EC-TYPE EXAMINATION CERTIFICATE relates only to design, examination and testing of the specified component in accordance to the directive 94/9/EC. If applicable, further requirements of the Directive apply to the manufacture and supply of this component.

(12) The marking of the component shall include following:



**I M 2 Ex d I
II 2G Ex d IIC
II 2D Ex tD**

This EC-Type Examination Certificate is valid till: **31 March 2012**

Responsible person:

Dipl. Ing. Šindler Jaroslav
Head of certification body



Date of issue: 07 March 2007

Number of pages: 4
Number of pages: 1/4

This certificate is granted subject to the general conditions of the Physical Technical Testing Institute.
This certificate may only be reproduced in its entirety and without any change, schedule included.



PHYSICAL TECHNICAL TESTING INSTITUTE

Ostrava-Radvanice

(13)

Schedule

(14) **EC-Type Examination Certificate N° FTZÚ 07 ATEX 0002U**

(15) Description of Component:

XD-SI universal instrument housing is designed to accommodate different electronics instruments or devices for working in hazardous areas with flammable gases, vapours and dusts. The housing and cover are made as stainless steel investment casting.

There are three flameproof joints in XD-SI instrument body:

- On the cover is used thread M100x2/6H;
- D₂, D₃ on the conduit openings for cable gland (various type of threaded holes);
- D₁ on process opening for thermowell (D₁ - various type of threaded holes).

The cover is locked by screw with hex socket using hex spanner. Each cover is sealed with "O" ring.

The unused holes can be blinded with a certified stopping plug.

(16) Report No. : 07/0002

(17) Schedule of Limitations:

17.1 -50°C < T_{serv} > 150°C for connection head with "O" ring made from VQM rubber (silicone)

17.2 IP protection 66 ÷ 68 – is depend on applied cable gland. (IP 68 – deep 1 m).

17.3 Max. dissipation power for temperature class are as follow:

Max. power dissipation (W)				
T _{amb}	Temperature class T6 85°C	Pztr (W)	Temperature class T5 100°C	Pztr (W)
		For all variety of enclosures position horizontally/vertically		For all variety of enclosures position horizontally/vertically
40°C	Δ θ ≤ 40 K	14,7 / 14,3	Δ θ ≤ 55 K	21,8 / 21,4
55°C	Δ θ ≤ 25 K	8,3 / 8,1	Δ θ ≤ 40 K	14,7 / 14,3
70°C	Δ θ ≤ 10 K	2,3 / 2,3	Δ θ ≤ 25 K	8,3 / 8,1
85°C	N.A.	- / -	Δ θ ≤ 10 K	2,3 / 2,3

(18) Essential Health and Safety Requirements:

Covered by standards mentioned in (9) of this certificate.

Responsible person:

Dipl. Ing. Sindler Jaroslav
Head of certification body



Date of issue: 07 March 2007

Page: 2/4

This certificate is granted subject to the general conditions of the Physical Technical Testing Institute.
This certificate may only be reproduced in its entirety and without any change, schedule included.



PHYSICAL TECHNICAL TESTING INSTITUTE
Ostrava-Radvanice

(13)

Schedule

(14) **EC-Type Examination Certificate N° FTZÚ 07 ATEX 0002U**

(19)

LIST OF DOCUMENTATION

- Application manual N-L3625 dated 18.12.2006
- Catalogue sheets for model: XD-SI dated 03.2007
- Drawings N°: 2-Z-L3586 dated 03.01.2007
- Stainless Steel Specification: 1.4301 AISI 304
1.4541 AISI 321
1.4401 AISI 316
- Silicone rubber specification ELASTOSIL R701/40-R701/80

Responsible person:

Dipl. Ing. Šindler Jaroslav
Head of certification body



Date of issue: 07 March 2007

Page: 3/4

This certificate is granted subject to the general conditions of the Physical Technical Testing Institute.
This certificate may only be reproduced in its entirety and without any change, schedule included.



PHYSICAL TECHNICAL TESTING INSTITUTE
Ostrava-Radvanice

(13)

Schedule

(14) EC-Type Examination Certificate N° FTZÚ 07 ATEX 0002U

(20)

TYPE KEY



TYPE OF INSTRUMENT
HOUSING

SYMBOL OF CONDUIT THREAD $D_3 - D_2$

M2 = M20x1,5 6H

M24 = M24x1.5 6H

M25 = M25x1.5 6H

G2 = G 1/2, BSP 1/2

G3 = G 3/4, BSP 3/4

N2 = 1/2 NPTmod – modified ac. to OIT-17/03

N3 = 3/4 NPTmod – modified ac. to OIT-17/03

PD = plugged

Notice:

Type: "size of thread / PD" if thread is plugged ex.
M2/PD, etc.

SYMBOL OF PROCESS THREAD D_1

M2 = M20x1,5 6H

M24 = M24x1.5 6H

M25 = M25x1.5 6H

M27 = M27x2 6H

G2 = G 1/2, BSP 1/2

G3 = G 3/4, BSP 3/4

N2 = 1/2 NPTmod – modified ac. to OIT-17/03

N3 = 3/4 NPTmod – modified ac. to OIT-17/03

PD = plugged

Notice:

Type: "size of thread / PD" if thread is plugged ex.
M2/PD, etc.

